
## Data From the CFT/CPS Trigger to the L2 Preprocessors



Data - 50 Tracks, 20 bits / track

Most of the time this link sits IDLE during which time it sends  $\underline{\mathsf{null}}$  frames .

Some time after a L1 accept is issued the data starts.

Word	Data
1	Source ID - Cross #
2	Turn #
3	1st Track
4	2nd Track
-	-
n-1	last Track
n	Number of Tracks Sent

The data words from L2 Concentrator. The data consists of two header words followed by n-3 tracks followed by the number of tracks. The maximum number of tracks is fixed and is NOW believed to be 50.

Immediately after the last track is sent the link returns to sending null frames.

	Format of 1st Data Word from CFT Front End				
Bit 7	Bit # Field Bit # Use				
19	Most Sig.	3	msb	spare	
18		2		spare	
17		1		spare	
16		0		spare	
15		7		spare	
14		6		spare	
13		5		spare	
12		4		spare	
11		3		spare	
10		2		spare	
9		1		spare	
8		0	Isb	Status	
7		7	msb	Crossing Number	
6		6		Crossing Number	
5		5		Crossing Number	
4		4		Crossing Number	
3		3		Crossing Number	
2		2		Crossing Number	
1		1		Crossing Number	
0	Least Sig.	0	Isb	Crossing Number	

bit format for the 1st word from the L2 Concentrator

	Format of	2nd	Data \	Word from CFT Front End	
Bit # Field Bit # Use					
19	Most Sig.	3		Spare	
18		2		Spare	
17		1		Spare	
16		0		Spare	
15		15	msb	Turn Number	
14		14		Turn Number	
13		13		Turn Number	
12		12		Turn Number	
11		11		Turn Number	
10		10		Turn Number	
9		9		Turn Number	
8		8		Turn Number	
7		7		Turn Number	
6		6		Turn Number	
5		5		Turn Number	
4		4		Turn Number	
3		3		Turn Number	
2		2		Turn Number	
1		1		Turn Number	
0	Least Sig.	0	Isb	Turn Number	

bit format for the 2<sup>nd</sup> word from the L2 Concentrator

	Format of Data Words from CFT Front End						
Bit a	Bit # Field Bit # Use						
19	Most Sig.	0		Track Found Flag [1=found]			
18		3			shold Track		CPS cluster
17		2			shold Track		CPS cluster
16		1		Low Thres	hold Track	CPS cluster	
15		0		Low Threshold Track N / S			CPS cluster
14		0			Pt for Trac		
13		3	msb	Inner (A) L	ayer Offset	t from Outer I	Layer Bin
12		2					
11		1					
10		0	Isb				
9		9	msb	Extended (	Outer (H) L	ayer Phi Bin	
8		8					
7		7					
6		6					
5		5		Outer (H) I	_ayer Phi B	in	
4		4					
3		3					
2		2					
1		1					
0	Least Sig.	0	Isb				

Definition of bits for the 20bit CFT/CPS track word.

Ten bits are used to identify the phi position.

Five bits are used to identify the momentum including its sign.

Four bits are used to identify matches with the CPS.

And one bit is used to tag the word as containing valid track information.

	Format of	Las	t Data	Word from CFT Front End
Bit # Field Bit #			Bit#	Use
19	Most Sig.	3		Spare
18		2		Spare
17		1		Spare
16		0		Spare
15		7	msb	Status
14		6		Status
13		5		Status
12		4		Status
11		3		Status
10		2		Status
9		1		Status
8		0	Isb	Status
7		7	msb	Number of Tracks Sent
6		6		Number of Tracks Sent
5		5		Number of Tracks Sent
4		4		Number of Tracks Sent
3		3		Number of Tracks Sent
2		2		Number of Tracks Sent
1		1		Number of Tracks Sent
0	Least Sig.	0	Isb	Number of Tracks Sent

bit format for the final word from the L2 Concentrator

The Crossing and Turn numbers are used to check that the correct event was sent to the L2pp. The L2pp is responsible for checking this and taking appropriate action. NO checking has been done prior to the L2pp.

The G-Link sends parity bits and is self-checking. If the G-Link receiver detects any error the L2pp is responsible for taking appropriate action. (error message to host, resetting link, ...)